

# #204 Everlock Primer - Product Data Sheet



## Description

Everlock #204 is a fast drying, easy to apply primer for concrete slabs before installing tile or wood flooring. It increases the adhesion of and enhances the performance of Everlock #205 and Everlock #800 asphalt mastics.

## Typical Physical Properties

Consistency	Liquid, apply with squeegee or brush
Average drying time to touch @ 77°F/25°C, minutes (Based on 8 mils wet film thickness)	30
Volume percent solids, %	42
Flash point (ASTM D3143)	65°F/18°C
Service temperature range	-20° to +200°F/-28° to +93°C
Weight per gallon	7.1 lbs.
Weight per liter	.85 kg
Dry film characteristics	Non-tacky, firm, glossy
Chemical resistance to acids, alkalis and salt spray	Good

## Application

The surfaces should be clean and dry. The product should be stirred well, and it should not be thinned. It should be poured onto the concrete slab and spread with squeegee to form a thin even coat. The Everlock Primer should be allowed to dry completely before application of Everlock #205 or Everlock #800 asphalt mastic adhesives for wood flooring.

## Coverage

Coverage may vary depending on the porosity of the slab; typical coverage is 400 square feet per gallon.

Packaging		
Size of Container	Approx. Weight	Units per pallet
5 gallon (19l) pail	39 lbs. (17.73 Kg)	36

## Storage and Handling

The work area should be well ventilated with no sources of ignition in the vicinity. For best results, the temperature should be 65°F and rising. The container should be kept tightly sealed and away from sources of ignition.

## Clean-up

Asphalt stains can be removed with non-hazardous, bio-degradable cleaners. Waterless hand cleaner should be used on skin, following the cleaner manufacturer's instructions carefully. Flammable or combustible petroleum based solvents should not be used.

## Advantages

- Proven performance; Everlock #204 has been used for over 25 years to prime concrete surfaces.
- Fast drying time
- Increases the protection against water intrusion given by Everlock #205 and Everlock #800 asphalt mastics
- Greatly increases the adhesion of asphalt mastics to concrete
- Easy cold application
- Non-chlorinated solvents

## Martin Asphalt Quality

Through Martin Asphalt, you get **Everything Asphalt**—a full range of products, including flooring adhesives for vinyl tile and wood flooring. In addition, you receive technical assistance in selecting the right materials and application. The company's AASHTO Certified Laboratory makes sure the products meet your specifications. And your products are delivered both on spec and on time via Martin's Gulf Coast network of production plants, storage facilities and transportation fleet including ocean-going and inland barges, rail cars and tanker trucks. For more information, contact us.